

光学特性データ

Sample	ファイヤーホーク G3(FH)
Data	: 07.01.12

STD. WHITE	=	180
PG (H)	=	1.25
PG (V)	=	0.00
α (H) R	=	+30.00°
α (H) L	=	-25.00°
α (V) R	=	+ 0.00°
α (V) L	=	- 0.00°
β (H) R	=	+45.00°
β (H) L	=	-40.00°
β (V) R	=	+ 0.00°
β (V) L	=	- 0.00°

(α) = 半値角($^{\circ}$ -ゲインの1/2の値)
 (β) = 1/3角($^{\circ}$ -ゲインの1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	21.00	0.12	+ 2.5°	225.00	1.25
- 80.0°	26.00	0.14	+ 5.0°	221.00	1.23
- 75.0°	29.00	0.16	+ 10.0°	214.00	1.19
- 70.0°	32.00	0.18	+ 15.0°	191.00	1.06
- 65.0°	38.00	0.21	+ 20.0°	166.00	0.92
- 60.0°	41.00	0.23	+ 25.0°	140.00	0.78
- 55.0°	46.00	0.26	+ 30.0°	110.00	0.62
- 50.0°	54.00	0.30	+ 35.0°	93.00	0.52
- 45.0°	64.00	0.36	+ 40.0°	80.00	0.44
- 40.0°	77.00	0.43	+ 45.0°	67.00	0.37
- 35.0°	90.00	0.50	+ 50.0°	57.00	0.32
- 30.0°	110.00	0.61	+ 55.0°	50.00	0.28
- 25.0°	139.00	0.77	+ 60.0°	43.00	0.24
- 20.0°	162.00	0.90	+ 65.0°	40.00	0.22
- 15.0°	189.00	1.05	+ 70.0°	33.00	0.18
- 10.0°	208.00	1.16	+ 75.0°	30.00	0.17
- 5.0°	220.00	1.22	+ 80.0°	27.00	0.15
- 2.5°	224.00	1.24	+ 85.0°	22.00	0.12

