

光学特性データ

Sample : LUMIFLEX-180
 Data : 97.03.17

STD . WHITE = 180
PG (H) = 1.92
PG (V) = 0.00
(H) R = + 30.00°
(H) L = - 25.00°
(V) R = + 0.00°
(V) L = - 0.00°
(H) R = + 45.00°
(H) L = - 40.00°
(V) R = + 0.00°
(V) L = - 0.00°

() = 半値角(ビーム径の1/2の値)
 () = 1/3角(ビーム径の1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	10.00	0.06	+ 2.5°	343.00	1.91
- 80.0°	20.00	0.11	+ 5.0°	336.00	1.87
- 75.0°	45.00	0.25	+ 10.0°	311.00	1.73
- 70.0°	58.00	0.32	+ 15.0°	275.00	1.53
- 65.0°	64.00	0.36	+ 20.0°	234.00	1.30
- 60.0°	72.00	0.40	+ 25.0°	198.00	1.10
- 55.0°	80.00	0.44	+ 30.0°	167.00	0.93
- 50.0°	90.00	0.50	+ 35.0°	142.00	0.79
- 45.0°	103.00	0.57	+ 40.0°	120.00	0.67
- 40.0°	120.00	0.67	+ 45.0°	104.00	0.58
- 35.0°	141.00	0.78	+ 50.0°	91.00	0.51
- 30.0°	167.00	0.93	+ 55.0°	81.00	0.45
- 25.0°	199.00	1.11	+ 60.0°	72.00	0.40
- 20.0°	236.00	1.31	+ 65.0°	66.00	0.37
- 15.0°	277.00	1.54	+ 70.0°	52.00	0.29
- 10.0°	313.00	1.74	+ 75.0°	29.00	0.16
- 5.0°	339.00	1.88	+ 80.0°	9.00	0.05
- 2.5°	346.00	1.92	+ 85.0°	5.00	0.03

