

光学特性データ

Sample : MALIBU

Data : 00.10.13

STD . WHITE	=	180
PG (H)	=	1.35
PG (V)	=	0.00
(H) R	=	+ 75.00°
(H) L	=	- 75.00°
(V) R	=	+ 0.00°
(V) L	=	- 0.00°
(H) R	=	+ 00.00°
(H) L	=	- 00.00°
(V) R	=	+ 0.00°
(V) L	=	- 0.00°

() = 半値角(ビークインの1/2の値)

() = 1/3角(ビークインの1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	84.00	0.52	+ 2.5°	234.00	1.35
- 80.0°	107.00	0.64	+ 5.0°	226.00	1.31
- 75.0°	119.00	0.71	+ 10.0°	206.00	1.19
- 70.0°	126.00	0.75	+ 15.0°	190.00	1.11
- 65.0°	132.00	0.78	+ 20.0°	176.00	1.03
- 60.0°	136.00	0.81	+ 25.0°	166.00	0.97
- 55.0°	139.00	0.82	+ 30.0°	158.00	0.93
- 50.0°	142.00	0.84	+ 35.0°	153.00	0.90
- 45.0°	145.00	0.86	+ 40.0°	149.00	0.88
- 40.0°	149.00	0.88	+ 45.0°	145.00	0.86
- 35.0°	153.00	0.90	+ 50.0°	143.00	0.84
- 30.0°	159.00	0.93	+ 55.0°	139.00	0.82
- 25.0°	167.00	0.98	+ 60.0°	136.00	0.81
- 20.0°	178.00	1.04	+ 65.0°	132.00	0.78
- 15.0°	191.00	1.11	+ 70.0°	127.00	0.76
- 10.0°	206.00	1.19	+ 75.0°	119.00	0.71
- 5.0°	225.00	1.30	+ 80.0°	108.00	0.65
- 2.5°	234.00	1.35	+ 85.0°	87.00	0.53

