

光学特性データ

Sample : MONOBLOX REAR

Data : 03.09.26

STD. WHITE = 180
PG (H) = 1.92
PG (V) = 0.00
(H) R = + 25.00°
(H) L = - 20.00°
(V) R = + 0.00°
(V) L = - 0.00°
(H) R = + 35.00°
(H) L = - 30.00°
(V) R = + 0.00°
(V) L = - 0.00°

() = 半値角(ビークゲインの1/2の値)
 () = 1/3角(ビークゲインの1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	10.00	0.06	+ 2.5°	330.00	1.83
- 80.0°	22.00	0.12	+ 5.0°	319.00	1.77
- 75.0°	35.00	0.19	+ 10.0°	282.00	1.57
- 70.0°	43.00	0.24	+ 15.0°	239.00	1.33
- 65.0°	49.00	0.27	+ 20.0°	200.00	1.11
- 60.0°	55.00	0.31	+ 25.0°	164.00	0.91
- 55.0°	65.00	0.36	+ 30.0°	135.00	0.75
- 50.0°	76.00	0.42	+ 35.0°	111.00	0.62
- 45.0°	90.00	0.50	+ 40.0°	84.00	0.47
- 40.0°	111.00	0.62	+ 45.0°	77.00	0.43
- 35.0°	135.00	0.75	+ 50.0°	66.00	0.37
- 30.0°	164.00	0.91	+ 55.0°	57.00	0.32
- 25.0°	201.00	1.12	+ 60.0°	49.00	0.27
- 20.0°	241.00	1.34	+ 65.0°	43.00	0.24
- 15.0°	283.00	1.57	+ 70.0°	33.00	0.18
- 10.0°	320.00	1.78	+ 75.0°	18.00	0.10
- 5.0°	342.00	1.90	+ 80.0°	10.00	0.06
- 2.5°	345.00	1.92	+ 85.0°	10.00	0.06

