

光学特性データ

Sample : リアソフトスタンダード RS-12K
 Data : 97.11.21

STD . WHITE =	180
PG (H) =	1.29
PG (V) =	0.00
(H) R =	+ 35.00°
(H) L =	- 25.00°
(V) R =	+ 0.00°
(V) L =	- 0.00°
(H) R =	+ 50.00°
(H) L =	- 45.00°
(V) R =	+ 0.00°
(V) L =	- 0.00°

() = 半値角(ビーム径の1/2の値)
 () = 1/3角(ビーム径の1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	10.00	0.06	+ 2.5°	229.00	1.27
- 80.0°	10.00	0.06	+ 5.0°	222.00	1.23
- 75.0°	15.00	0.08	+ 10.0°	201.00	1.12
- 70.0°	36.00	0.20	+ 15.0°	177.00	0.98
- 65.0°	55.00	0.31	+ 20.0°	154.00	0.86
- 60.0°	63.00	0.35	+ 25.0°	134.00	0.74
- 55.0°	69.00	0.38	+ 30.0°	115.00	0.64
- 50.0°	76.00	0.42	+ 35.0°	100.00	0.56
- 45.0°	86.00	0.48	+ 40.0°	88.00	0.49
- 40.0°	97.00	0.54	+ 45.0°	78.00	0.43
- 35.0°	111.00	0.62	+ 50.0°	69.00	0.38
- 30.0°	128.00	0.71	+ 55.0°	62.00	0.34
- 25.0°	149.00	0.83	+ 60.0°	57.00	0.32
- 20.0°	172.00	0.96	+ 65.0°	51.00	0.28
- 15.0°	195.00	1.08	+ 70.0°	43.00	0.24
- 10.0°	218.00	1.21	+ 75.0°	28.00	0.16
- 5.0°	232.00	1.29	+ 80.0°	10.00	0.06
- 2.5°	233.00	1.29	+ 85.0°	10.00	0.06

