

光学特性データ

Sample : リアソフトスタンダード RS-13K

Data : 00.06.15

| | |
|---------------|----------|
| STD . WHITE = | 180 |
| PG (H) = | 1.86 |
| PG (V) = | 0.00 |
| (H) R = | + 15.00° |
| (H) L = | - 15.00° |
| (V) R = | + 0.00° |
| (V) L = | - 0.00° |
| (H) R = | + 25.00° |
| (H) L = | - 20.00° |
| (V) R = | + 0.00° |
| (V) L = | - 0.00° |

() = 半値角(ビークの1/2の値)

() = 1/3角(ビークの1/3の値)

| HORIZONTAL | | | | | |
|------------|--------|------|---------|--------|------|
| Angle | nt | Gs | Angle | nt | Gs |
| - 85.0° | 10.00 | 0.06 | + 2.5° | 335.00 | 1.86 |
| - 80.0° | 14.00 | 0.08 | + 5.0° | 306.00 | 1.70 |
| - 75.0° | 35.00 | 0.19 | + 10.0° | 228.00 | 1.27 |
| - 70.0° | 42.00 | 0.23 | + 15.0° | 174.00 | 0.97 |
| - 65.0° | 45.00 | 0.25 | + 20.0° | 135.00 | 0.75 |
| - 60.0° | 48.00 | 0.27 | + 25.0° | 110.00 | 0.61 |
| - 55.0° | 51.00 | 0.28 | + 30.0° | 90.00 | 0.50 |
| - 50.0° | 55.00 | 0.31 | + 35.0° | 79.00 | 0.44 |
| - 45.0° | 60.00 | 0.33 | + 40.0° | 70.00 | 0.39 |
| - 40.0° | 67.00 | 0.37 | + 45.0° | 62.00 | 0.34 |
| - 35.0° | 75.00 | 0.42 | + 50.0° | 57.00 | 0.32 |
| - 30.0° | 86.00 | 0.48 | + 55.0° | 52.00 | 0.29 |
| - 25.0° | 104.00 | 0.58 | + 60.0° | 49.00 | 0.27 |
| - 20.0° | 127.00 | 0.71 | + 65.0° | 46.00 | 0.26 |
| - 15.0° | 159.00 | 0.88 | + 70.0° | 38.00 | 0.21 |
| - 10.0° | 207.00 | 1.15 | + 75.0° | 30.00 | 0.17 |
| - 5.0° | 278.00 | 1.54 | + 80.0° | 14.00 | 0.08 |
| - 2.5° | 318.00 | 1.77 | + 85.0° | 10.00 | 0.08 |

