

光学特性データ

Sample : スノーマット100

Data : 00.07.24

STD . WHITE =	180
PG (H) =	1.06
PG (V) =	0.00
(H) R =	+ 85.00°
(H) L =	- 85.00°
(V) R =	+ 0.00°
(V) L =	- 0.00°
(H) R =	+ 0.00°
(H) L =	- 0.00°
(V) R =	+ 0.00°
(V) L =	- 0.00°

() = 半値角(ビークの1/2の値)

() = 1/3角(ビークの1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	79.00	0.44	+ 2.5°	191.00	1.06
- 80.0°	112.00	0.62	+ 5.0°	178.00	0.99
- 75.0°	121.00	0.67	+ 10.0°	169.00	0.94
- 70.0°	124.00	0.69	+ 15.0°	160.00	0.89
- 65.0°	130.00	0.72	+ 20.0°	155.00	0.86
- 60.0°	131.00	0.73	+ 25.0°	149.00	0.83
- 55.0°	133.00	0.74	+ 30.0°	146.00	0.81
- 50.0°	137.00	0.76	+ 35.0°	142.00	0.79
- 45.0°	139.00	0.77	+ 40.0°	140.00	0.78
- 40.0°	140.00	0.78	+ 45.0°	139.00	0.77
- 35.0°	142.00	0.79	+ 50.0°	137.00	0.76
- 30.0°	146.00	0.81	+ 55.0°	133.00	0.74
- 25.0°	148.00	0.82	+ 60.0°	131.00	0.73
- 20.0°	153.00	0.85	+ 65.0°	130.00	0.72
- 15.0°	158.00	0.88	+ 70.0°	126.00	0.70
- 10.0°	166.00	0.92	+ 75.0°	121.00	0.67
- 5.0°	176.00	0.98	+ 80.0°	112.00	0.62
- 2.5°	187.00	1.04	+ 85.0°	79.00	0.44

