

光学特性データ

Sample : TECHPLEX-150
 Data : 99.04.08

STD . WHITE = 180
PG (H) = 1.39
PG (V) = 0.00
(H) R = + 30.00°
(H) L = - 30.00°
(V) R = + 0.00°
(V) L = - 0.00°
(H) R = + 45.00°
(H) L = - 40.00°
(V) R = + 0.00°
(V) L = - 0.00°

() = 半値角(ビーム径の1/2の値)
 () = 1/3角(ビーム径の1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	10.00	0.06	+ 2.5°	251.00	1.39
- 80.0°	12.00	0.07	+ 5.0°	248.00	1.38
- 75.0°	31.00	0.17	+ 10.0°	232.00	1.29
- 70.0°	40.00	0.22	+ 15.0°	209.00	1.16
- 65.0°	45.00	0.25	+ 20.0°	182.00	1.01
- 60.0°	51.00	0.28	+ 25.0°	155.00	0.86
- 55.0°	57.00	0.32	+ 30.0°	132.00	0.73
- 50.0°	66.00	0.37	+ 35.0°	112.00	0.62
- 45.0°	76.00	0.42	+ 40.0°	93.00	0.52
- 40.0°	88.00	0.49	+ 45.0°	82.00	0.46
- 35.0°	105.00	0.58	+ 50.0°	70.00	0.39
- 30.0°	124.00	0.69	+ 55.0°	61.00	0.34
- 25.0°	146.00	0.81	+ 60.0°	54.00	0.30
- 20.0°	172.00	0.96	+ 65.0°	48.00	0.27
- 15.0°	199.00	1.11	+ 70.0°	36.00	0.20
- 10.0°	223.00	1.24	+ 75.0°	19.00	0.11
- 5.0°	243.00	1.35	+ 80.0°	10.00	0.06
- 2.5°	249.00	1.38	+ 85.0°	10.00	0.06

