

光学特性データ

Sample : ULTRAMATTE-200

Data : 97.03.17

STD . WHITE =	180
PG (H) =	1.88
PG (V) =	0.00
(H) R =	+ 30.00°
(H) L =	- 25.00°
(V) R =	+ 0.00°
(V) L =	- 0.00°
(H) R =	+ 80.00°
(H) L =	- 80.00°
(V) R =	+ 0.00°
(V) L =	- 0.00°

() = 半値角(ビークの1/2の値)

() = 1/3角(ビークの1/3の値)

HORIZONTAL					
Angle	nt	Gs	Angle	nt	Gs
- 85.0°	86.00	0.48	+ 2.5°	322.00	1.79
- 80.0°	122.00	0.68	+ 5.0°	296.00	1.64
- 75.0°	136.00	0.76	+ 10.0°	238.00	1.32
- 70.0°	143.00	0.79	+ 15.0°	204.00	1.13
- 65.0°	148.00	0.82	+ 20.0°	182.00	1.01
- 60.0°	151.00	0.84	+ 25.0°	172.00	0.96
- 55.0°	154.00	0.86	+ 30.0°	166.00	0.92
- 50.0°	156.00	0.87	+ 35.0°	162.00	0.90
- 45.0°	158.00	0.88	+ 40.0°	159.00	0.88
- 40.0°	160.00	0.89	+ 45.0°	157.00	0.87
- 35.0°	163.00	0.91	+ 50.0°	155.00	0.86
- 30.0°	168.00	0.93	+ 55.0°	153.00	0.85
- 25.0°	175.00	0.97	+ 60.0°	150.00	0.83
- 20.0°	189.00	1.05	+ 65.0°	146.00	0.81
- 15.0°	214.00	1.19	+ 70.0°	142.00	0.79
- 10.0°	255.00	1.42	+ 75.0°	134.00	0.74
- 5.0°	312.00	1.73	+ 80.0°	121.00	0.67
- 2.5°	338.00	1.88	+ 85.0°	99.00	0.55

